



FMT 50 PP Flow Meter



More than just pumps.

FLUX FMT 50 PP Flow Meter



The FMT 50 PP uses an interlocked impeller in the measuring chamber which guarantees fast and safe filling. Suitable for use with low viscosity liquids in conjunction with our JUNIORFLUX & COMBIFLUX pumps, as well as in fixed installations. *(Not suitable for use with flammable liquids)*

Benefits: User-friendly interface for fast and easy calibration. 5-digit LCD-Display allows for easy reading of batch readout, totalizing information and unit of measure.

| Type | FMT 50 PP |
|-----------------------------------|---------------------------------------|
| Flowrate | 1.3 - 13.2 GPM (5 - 50 L/min) |
| Operating pressure at 68°F (20°C) | 58 PSIG (4 bar) |
| Viscosity | 40 cPs Max |
| Operating temperature | 14 - 122°F (-10 - 50 °C) |
| Accuracy (not calibrated) | ± 2 % |
| Accuracy (calibrated) | ± 1 % |
| Inlet-outlet connections* | Inlet G1(1" BSP), Outlet G1A (1" BSP) |
| Material: housing | Polypropylene (PP) |
| Material: seal | FKM |
| Protection | IP65 |
| Weight | 0.6 lbs (0.3 kg) |
| Part No. | A0500003 |

* NPT Adapters available

Contact us for more information on FLUX flow meters, as well as COMBIFLUX & JUNIORFLUX pumps. We will be more than happy to assist with your application and equipment selection.



More than just pumps

FLUX PUMPS CORPORATION
300 Townpark Drive, Suite 110
Kennesaw, GA 30144, USA
Phone 800-367-3589
info@fluxpumpsusa.com
www.fluxpumpsusa.com